


MOD. VB270M




Specifiche tecniche




MOD	FORATURA DRILLING ISO 5211 FLANGE	CH	A	B	C	D	E	F	G	H	I	L	M	N	O	P	Q	R	S	T
MOD. VB270M	F07-F10	22	139	83	35	279	184	95	175	275	109	166	314	247	67	24	70	102	M8X15	M10X15

Diagrammi elettrici


SCHEMA ELETTRICO DAL VB030 AL VB350 e DAL VB015M AL VB350M 12V AC/DC 50/60 Hz, 24V AC/DC 50/60 Hz, 100-240V AC 50/60 Hz
ELECTRIC WIRING FROM VB030 TO VB350 AND FROM VB015M TO VB350M 12V AC/DC 50/60 Hz, 24V AC/DC 50/60 Hz, 100-240V AC 50/60 Hz



SCHEMA ELETTRICO CON POSIZIONATORE DAL VB030 AL VB350 e DAL VB015M AL VB350M 12V AC/DC 50/60 Hz, 24V AC/DC 50/60 Hz, 100-240V AC 50/60 Hz
ELECTRIC WIRING WITH POSITIONER FROM VB030 TO VB350 AND FROM VB015M TO VB350M 12V AC/DC 50/60 Hz, 24V AC/DC 50/60 Hz, 100-240V AC 50/60 Hz



SCHEMA ELETTRICO CON POSIZIONE INTERMEDIA DAL VB030 AL VB350 E DAL VB030M AL VB350M 24V AC/DC 50/60Hz, 100-240V AC 50/60Hz
ELECTRIC WIRING WITH MIDDLE POSITION FROM VB030 TO VB350 AND FROM VB030M TO VB350M 24V AC/DC 50/60Hz, 100-240V AC 50/60Hz



Applicazioni



FOOD &
BEVERAGE



HVAC



PAINTS &
SOLVENTS



WATER
TREATMENT



CHEMICAL



OEM



MARINE